

State Environment Impact Assessment Authority, M.P. (Government of India, Ministry of Environment, Forest & Climate Change)

Environmental Planning Coordination Organization (EPCO)
Paryavaran Parisar, E-5. Arera Colony
Bhopal-4620 16
visit us http://www.mpseiaa.nic.in

Tel:0755-2466970, 2466859 Fax: 0755-2462136

No: 2/25 SEIAA/2019 Date: 1. 2.19

To, District Judge, Indore. District & Sessions Court, Indore (MP)- 452001

Sub:- Case No 5804/2018: Prior Environmental Clearance for District Court Indore of District & Sessions Court, Indore, (M.P) Khasra no. 526/1/1, 526/1/2 at Village Pipliyahana Tehsil & District Indore, MP. Total plot area- 1, 23,700 sq.m. (12.37 ha).Total Built up area – 1,35,763.00 sq.m.by District Judge, Indore., through District & Session Judge District Judge Chandresh Kumar Khare, District & Sessions Court, Indore 452001 - Email ck.khare@mphc.in Telephone No. +91- 9425156382 Envt. Consultant:In-situ enviro care

Ref: Your application dtd. 18.12.2018 received in SEIAA office on 19.12.2018.

With reference to above the proposal has been appraised as per prescribed procedure & provisions under the EIA notification issued by the Ministry of Environment & Forests vide S.O. 1533 (E), dated 14th September 2006 and its amendment, on the basis of the mandatory documents enclosed with the application viz., Form I, Form IA, Conceptual Plan, drawings and subsequently submission of PPT & the additional clarifications furnished in response to the observations of the State Expert Appraisal Committee (SEAC) and State Environment Impact Assessment Authority (SEIAA) constituted by the competent Authority.

- (i). The proposed project is building & construction project for court building at Khasara No. 526/1/1, 526/1/2, Village-Pipliahana, Tehsil & District Indore (MP). The project involves the construction of 169 Courtroom Building, Amenity Block, Service Block and other ancillaries.
- (ii). As per the T & CP Indore (vide let no. 8688/NAGRANI/2018 dtd. 06.10.2018) the total land area is 12.370 ha. The total built up area proposed by PP is 1,35,763.00 sq.m. The project comes under 8 (a) category of schedule of EIA Notification, 2006 because total construction is between 20,000 sq.m. & 1, 50,000 sq.m and plot area is less than 50 ha.
- (iii). Earlier the environmental clearance was issued to PP dtd14.03.16 for case no, 4977/2016. However vide letter dtd.11.01.19 PP has requested to withdraw the earlier environmental clearance for the said project and accordingly the case no. 4977/2016 has been closed by the authority in its 519th meeting dtd. 11.01.19.
- (iv). Regarding land documents PP has submitted Nazul officer order dtd 22/24/02.2000 in which it is mentioned that the land 11.161 ha has been allocated for construction of Court and possession has been retained by the Registrar High Court, Indore (M.P). PP has also submitted copy of Khasra Panchsala 2014-15 for land ownership and IDA order dtd. 02.01.18 for additional land 7540.40 sq.m and 4982.80 for club house and STP respectively.

Case No.: To be quoted in registered cases for correspondence

1 of 11

- (v). The total water requirement is 530 KLD and fresh water requirement is 250 KLD. The total recycled water 280 KLD (140 KLD Flushing + 60 KLD Gardening+ 80 KLD air cooling units). The source of water supply is Indore Municipal Corporation. PP has submitted letter (19.11.18) from Nagar Nigam Indore for supply of water.
- (vi). The total waste water generation is 308 KLD. PP has provided sewage treatment plant of 310 KLD. The total treated waste water is 280 KLD. PP has proposed 100% recycle of treated waste water. PP has submitted letter (dtd. 19.11.18) from Nagar Nigam Indore for disposal of extra treated waste water in their already laid trunk sewer near the project site.
- (vii). Approximately 2500 kg per day Municipal Solid waste shall be generated which is proposed to be segregated at source and the biodegradable and non- recyclable/ non biodegradable waste will be stored and collected separately. There will separate MSW collection centre i.e. each for block. Colored collection bins shall be provided in proper numbers. Final disposal through Municipal Corporation Indore. PP has submitted NOC from Indore Municipal Corporation letter (dtd. 19.11.18) for disposal of solid waste.
- (viii). The storm water drainage planning is integral part of the proposed project. Adequate storm water channels at the site is provided in drainage design to ensure that the storm water runoff flow direction and drainage pattern remains unaffected during post construction/ operational phase. Thus, the existing Natural terrain/ topography will be maintained to ensure that there is no change in the land surface affecting drainages or run-off.
- (ix). The project is usually silence zone. However, Traffic management measurement will including modification of speed limits, restricting or prohibiting heavy vehicle traffic, regular maintenance of internal roads with proper circulation space will be ensured to have noticeable difference in noise & vibrations. For control of air pollution PP has proposed as follows:
 - a. Periodical stack monitoring will be carried out of all D.G. Set.
 - b. Ambient air quality of the proposed unit to be monitored.
 - c. Appropriate stack height will be provided.
 - d. Traffic controlled by trained staff.
- (x). PP has proposed to provide roof top rain water harvesting system with 10 nos. of recharging pits.
- (xi). PP has proposed the maximum height of the building is 40. However as per T & CP approval the height of the building is 36.0 m. PP has provided Front MOS 15 m and side/rear 7.5 m.
- (xii). For firefighting, PP has proposed that the entire building shall be provided with a fire suppression system comprising over head water storage tanks, dedicated fire pumps on terrace, hose reels, wet riser, yard hydrants and sprinkler system as per National Building code (NBC). Each Floor will have fire hydrant station and each lobby shall be provided with one set extinguisher. In the proposed project Alarm system shall be provided. An independent fire hydrant ring main is proposed to run around the buildings.
- (xiii). The total power requirement is 2270 KVA at 50% Diversity Factor. For backup source PP has proposed 3 Nos. D.G. Set (3 x 500 KVA) and 3 Nos. of 100 KVA each UPS. For energy conservation PP has proposed Level controller for pumps, Timer for street & Common lighting, Reduced in load due to using the LED Lights, Distribution Transformer are 3 star Rated as per BEE norms, Designing of peak & non peak circuits for common area and Solar powered street lights etc.
- (xiv). PP has proposed to provide 2584 ECS (1894+690) in basement, stilt and open area.

3/2

(xv). Out of the total land, 14,844 sq.m (12%) is proposed to be developed as green belt by planting 307 numbers of trees including ornamental plants.

Based on the information submitted at Para i to xv above and others, the State Level Environment Impact Assessment Authority (SEIAA) considered the case in its 519th meeting held on 11.01.2019 decided to accept the recommendations of 337th SEAC meeting held on dtd. 01.01.2019.

Hence, Environmental Clearance is accorded under the provisions of EIA notification dtd. 14th September 2006 and its amendments to the proposed "District Court Indore of District & Sessions Court, Indore, (M.P) Khasra no. 526/1/1, 526/1/2 at Village Pipliyahana Tehsil & District Indore, MP. Total plot area- 1, 23,700 sq.m. (12.37 ha). Total Built up area – 1,35,763.00 sq.m. by District Judge, Indore., through District & Session Judge District Judge Chandresh Kumar Khare, District & Sessions Court, Indore 452001 subject to the compliance of the Standard Conditions and the following additional Specific Conditions as recommended by SEIAA & SEAC in its meetings.

A. Specific Conditions as recommended by SEIAA:-

(1) The entire demand of water should be met through Municipal Corporation, Indore and there should be no extraction of ground water.

(2) Waste Water Management :-

- (a) Linkage with municipal sewer line for disposal of waste water.
- (b) The individual sewage disposal connection in the existing residential colony on the southern side has not been done resulting in flow of raw sewage in the Nalla which joins the existing water body. Municipal Corporation, Indore should ensure proper disposal of sewage into the main trunk line by providing individual domestic connections.
- (c) As the proposed building construction falls within the catchment area of water body, PP should leave rain water runoff channels within their property to ease flow of rain water from the eastern side. They should also make appropriate provision that the flow is uninterrupted and pass through a grit chamber or any other arrangement to arrest the debris etc entering the water body.
- (d) Water quality monitoring should be carried out regularly.
- (e) Presently on the eastern side from the IDA scheme, the internal sewer lines are leaking and the sewage is collected in small pits. IDA is hereby directed to maintain the sewer lines properly and connect it to the main sewer trunk.
- (f) Regarding the extent of the water body the directives of Hon'ble NGT shall be binding on the PP.

(3) For Rain Water Harvesting, and Ground water recharge:-

- (a) PP should ensure the rain water harvesting with 10 no. of recharging pits and these pits should be connected laterally to consume the surplus runoff. In addition, PP should provide recharging trenches. The base of the trenches should be Kachha with pebbles.
- (b) The storm water from roof top, paved surfaces and landscaped surfaces should be properly channelized to the rain water harvesting sumps through efficient storm water network as proposed. The budget should be included in EMP plan for storm water management.
- (c) Rain water harvesting for roof run- off and surface run- off, as plan submitted should be implemented. Before recharging the surface run off, pre-treatment must be done to remove suspended matter, oil and grease.



Case No. 5804/2018

Issued vide letter no. dated

(4) Solid Waste Management:

- (a) Provide compactors for MSW.
- (b) Ensure three bin systems for segregated collection of waste.
- (c) Ensure linkage with Municipal Corporation for final disposal of MSW.
- (5) PP should ensure to construct height of the building, road width, Front MOS and side / rear MOS and Open spaces as per approved layout of T&CP.

(6) For firefighting:-

- (a) PP should ensure connectivity to the fire station from the project site.
- (b) As per MPBVR, 2012 rule 42 (3) PP should submit necessary drawings and details to the Authority (Nagar Nigam, Indore) incorporating all the fire fighting measures recommended in National Building Code Part - IV point no. 3.4.6.1. The occupancy permit shall be issued by Nagar Nigam only after ensuring that all fire fighting measures are physically in place.

(7) For Energy Conservation PP should Ensure :-

- (a) To provide 3 Nos. D.G. Set (3 x 500 KVA) and 3 Nos. of 100 KVA each UPS.
- (b) Use of LED lights in the common areas, landscape areas, signage's, entry gates and boundary compound walls etc.
- (c) Solar lights provide for common amenities like Street lighting & Garden lighting.
- (d) PP should ensure installation of photovoltaic cells (solar energy) for lighting in common areas, LED light fixtures, and other energy efficient equipments.

(8) Air Quality and Noise:-

- (a) Dust, smoke & debris prevention measures such as wheel washing, screens, barricading & debris chute shall be installed at the site during construction including plastic/tarpaulin sheet covers for trucks bringing in sand & material at the site.
- (b) Periodical stack monitoring should be carried out of all D.G. Set.
- (c) Ambient air quality of the proposed unit should be monitored regularly.
- (d) Appropriate stack height should be provided.
- (9) PP should ensure to provide car parking (2584 ECS) as proposed.

(10) Green Belt:

- (a) PP should ensure to develop green belt area as recommended by SEAC.
- (b) Plantation should be done in two rows all along the periphery of the project area including Avenue plantation along the roads, trees of indigenous local varieties like Neem, Peepal, Kadam, Karanj, Kachnaar etc. along with ornamental varieties.
- (c) Every effort should be made to protect the existing trees on the plot.
- (11) Project Proponent shall ensure the compliance of the directions of Hon'ble National Green Tribunal and any other directions / order issued by the other Courts from time to time.

Specific Conditions as recommended by SEAC

(A) PRE-CONSTRUCTION PHASE

- 1. During construction, the entire area should be covered with 12 feet MS sheets .
- 2. Curtaining of site should also be carried out to protect nearby habitat.
- 3. For dust suppression, regular sprinkling of water should be undertaken
- 4. PP will obtain other necessary clearances/NOC from respective authorities.

Case No. 5804/2018 Issued vide letter no. dated

- 5. Provisions shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structure to be removed after completion of the period.
- The grant of Environmental Clearance should be subject necessary Wild Life Clearance from NBWL to be obtained by PP.

(B) CONSTRUCTION PHASE

- During construction phase, a settling tank should be provided before final discharge of the effluent.
- 8. No construction is permitted within 50 meters of FRL of catchment area of lake.
- 9. PPE's such as helmet, ear muffs etc should be provide to the workers.
- 10. Fire extinguishers should be provided on site during construction period.
- 11. Proper ventilation system shall be provided to all part of the work areas of site.
- 12. All dust producing construction materials will be transported with proper cover as tarpaulin.
- 13. Properly tuned construction machinery and good condition vehicles (low noise generating and having PUC certificate) should be used.
- 14. The area statement of the project site is as follows:

S.No.	Particular	Area (in Acre)	Area (in sq.m)
1.	Total Site Area	36.27	146779.48
2.	Reservoir Area	9.08	36745.5
3.	F.T.L area	9.37	37919
a.	Planning Area	13.93	56373
b.	Green Belt Area	4.27	17280.08
C.	Net Planning Area (a+b)	18.2	73653.08

- 15. Waste construction material should be recycles as far as possible and remaining should be disposed off at a designated place in consultation with the local authority.
- 16. Peripheral plantation all around the project boundary shall be carried out using tall saplings of minimum 2 meters height of species which are fast growing with thick canopy cover preferably of perennial green nature. As proposed in the plantation scheme minimum of 384 (307 trees if 80% survival rate) no's of trees will be planted. In the 2763 sq. m area. PP will also make necessary arrangements for the causality replacement and maintenance of the plants.
- 17. MSW storage area should have 48 hours storage capacity and MSW should be disposed off at a designated place in consultation with the local authority.
- 18. The rainwater harvesting structures will be total ground water recharge in tune of 8480 KL/Year.
- 19. Entire excavated soil shall be reused within the project site.
- 20. CFL/LED should be preferred over of tube lights.
- 21. Provision for physically challenged persons be made so that they easily excess pathway/derive way for their vehicles.
- 22. PP should explore the possibility of providing solar street light.
- 23. Waste oil generated from the DG sets (3 X 500 KVA with aquastic enclosures) should be disposed off in accordance with the Hazardous and Other Wastes (Management and Transboundary Movement) Rules, 2016 after obtaining authorization.

(C) POST CONSTRUCTION/OPERATIONAL PHASE

- 24. The total water requirement for the project is 530 KLD out of which fresh water requirement for the project shall not exceed 250 KLD and 280 KLD shall be found through recycled water.
- 25. The capacity of STP shall be capacity of 310 KLD, which is MBBR Based on Preliminary treatment and Aerobic biodegradation treatment followed by tertiary

Case No. 5804/2018

Issued vide letter no. dated



- treatment and zero liquid discharge condition shall be maintained as out of 280 KLD treated waste water, 140 KLD is proposed for flushing, 80 KLD for air cooling units and 60 KLD for landscape.
- 26. Efficient dual plumbing system shall be provided to achieve conservation of fresh water and utilization of treated effluent.
- 27. Fund should be exclusively earmarked for the implementation of EMP through a separate bank account.

(D) ENTIRE LIFE OF THE PROJECT

- 28. The total EMP cost is Rs. 1737.00 lakh as capital and Rs. 136.00 lakh/year as recurring expenses.
- 29. PP has proposed Rs. 1737 lacks for landscaping & green belt development and Rs.25 lacks/year for recurring expenses in the proposed EMP of this project.
- 30. As proposed, the green belt development / plantation activities should be completed within the first three years of the project and the proposed species should also be planted in consultation with the forest department.
- 31. The project authorities should comply with the provisions made in the Hazardous Waste (management, handling & Trans-boundary Movement) Rules 2016, Plastic Waste Management Rules 2016, E-waste (Management) Rules, 2016, Construction and Demolition Waste Management Rules, 2016 and Solid Waste Management Rules, 2016 etc.
- 32. In case of any, change in scope of work, technology, modernization and enhancement of capacity/ built-up area/ project area shall again require prior environmental clearance as per EIA notification, 2006.
- 33. The validity of the EC shall be as per the provisions of EIA Notification subject to the following: Expansion or modernization in the project, entailing capacity/ built-up area/ project area, addition with change in process and or technology and any change in product mix shall require a fresh Environment Clearance.

Standard Conditions:

A. Construction Phase

- 1. The construction site shall be provided with adequately barricades of at least 3 m height on its periphery with adequate signage.
- 2. All required sanitary and hygienic measures should be in place before starting any construction work and are to be maintained throughout the project phase.
- 3. Provision shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structures to be removed after the completion of the project.
- 4. Occupational health and safety measures for the workers including identification of work related health hazards, training on malaria eradication, HIV, and health effects on exposure to dust etc. shall be carried out. Periodic monitoring for exposure to respirable dust on the workers shall be conducted and records maintained including health records of the workers. Awareness programme for workers on impact of dust on their health and precautionary measures like use of personal equipments etc. shall be carried out periodically.



Case No. 5804/2018

Issued vide letter no. dated

- 5. A First Aid Room will be provided in the project both during construction and operation of the project.
- 6. All the topsoil excavated during construction activities should be stored for use in horticulture/landscape development within the project site.
- 7. Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
- 8. Soil and ground water samples will be tested to ascertain that there is no threat to ground water quality by leaching of heavy metals and other toxic contaminants.
- Construction spoils, including bituminous material and other hazardous materials, must not be allowed to contaminate water courses and the dump sites for such material must be secured so that they should not leach into the ground water.
- 10. Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the M.P. Pollution Control Board.
- 11. The diesel generator sets (if any) to be used during construction phase should be low sulphur diesel type and should conform to Environment (Protection) Rules prescribed for air and noise emission standards.
- 12. The diesel required (if any) for operating DG sets shall be stored in underground tanks and if required, clearance from Chief Controller of Explosives shall be taken.
- 13. Wastewater generated from temporary labor tents will be diverted to the sewer network in the area.
- 14. No water logging should take place at any point during construction phase.
- 15. If the project site is located within the 100 km of Thermal Power Stations, then fly ash should be used as building material in the construction as per the provisions of Fly ash Notification of September, 1999 and amended as on 27th August, 2003.
- 16. As far as possible ready mixed concrete should be used in construction work.
- 17. Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards and should be operated only during non-peak hours.
- 18. Ambient noise levels should conform to residential standards both during day and night. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB/ MPPCB.
- Storm water control and its use should be as per CGWB and BIS standards for various applications.
- 20. Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
- 21. Care shall be taken during the wet drilling activities.

dy.

Case No. 5804/2018

Issued vide letter no. dated

- 22. Spread of contaminated water should be prevented by installing temporary barriers of G.I. Sheets.
- 23. To prevent surface and ground water contamination by oil/grease, leak proof containers shall be used for storage and transportation of oil/grease. The floors of oil/grease handling area will be kept effectively impervious.
- 24. On-site burning of waste material will not be permitted.
- 25. Ground water should not be used during construction phase. Private tanker water suppliers may be asked to supply water during construction phase.
- 26. Fixtures for showers, toilet flushing and drinking should be of low flow either by use of aerators or pressure reducing devices or sensor based control.
- 27. Wherever possible, the area around the STP / ETP should be surrounded with dense green belt.
- 28. To reduce the electricity consumption and load on air conditioning, high quality double glass with special reflective coating in windows should be promoted.
- 29. Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfill requirement.
- 30. Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code which is proposed to be mandatory for all air-conditioned spaces while it is aspirational for non-air conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.
- 31. Approval of the competent authority shall be obtained for structural safety of the buildings due to earthquake, adequacy of fire fighting equipments, etc. as per National Building Code including protection measures from lightening etc.

B. Operation Phase

- 32. The installation of the Sewage Treatment Plant (STP) as submitted by PP in the office of SEIAA should be certified by an independent expert and a report in this regard should be submitted to the Regional office of the Ministry of Environment & Forest, Gol before the project is commissioned for operation. Treated effluent discharge from STP shall be recycled /reused to the maximum extent possible. Treated effluent shall conform to the norms and standards of the M.P. Pollution Control Board. Necessary measures should be made to mitigate the odour problem from STP.
- 33. Treated waste water should not be used for air conditioning.
- 34. Treatment of 100% grey water by decentralized treatment should be done.
- 35. The bio-medical waste (if applicable) generated should be disposed off as per the provisions of Bio-medical waste (Management and Handling) Rules 1988 as amended till date.
- 36. Provision of separate entrance / exit gate should be made for collection of segregated bio-medical waste (if applicable) from the storage area.
- 37. The solid waste generated should be properly collected and segregated. Wet garbage should be composted and dry/inert solid waste should be disposed off to the approved sites for land filling after recovering recyclable material as per CPCB norms.

A P

Case No. 5804/2018

Issued vide letter no. dated

- 38. Diesel power generating sets if proposed as source of back up power for elevators and common area illumination during operation phase should be of enclosed type and confirm to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. Low sulphur diesel must be used. The location of the DG sets may be decided with in consultation with Madhya Pradesh Pollution Control Board.
- 39. Any hazardous waste generated during operation phase, should be disposed off as per applicable rules and norms with necessary approvals of the M.P. Pollution Control Board.
- Noise should be controlled to ensure that it does not exceed the prescribed standards of CPCB.
- 41. Rain water harvesting for roof run- off and surface run- off, should be implemented. Before recharging the surface run off, pre-treatment must be done to remove suspended matter, oil and grease. The bore well for rainwater recharging should be kept at least 5 mts. above the highest ground water table.
- 42. The ground water level and its quality should be monitored regularly in consultation with Central Ground Water Authority.
- 43. Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking should be fully internalized and no public space should be utilized.
- 44. A Report on the energy conservation measures confirming to energy conservation norms finalize by Bureau of Energy Efficiency should be prepared incorporating details about building materials & technology, R & U Factors etc and submit to the Regional office of Ministry of Environment & Forest, GoI in three months time.
- 45. The area earmarked for the parking shall be used for parking only. No other activity shall be permitted in this area.
- 46. Ozone Depleting Substances (Regulation & Control) Rules shall be followed while designing the air conditioning system (if any) of the project.

C. Others

- 47. All activities / mitigative measures proposed by PP in Environmental Impact Assessment (if applicable) and approved by SEAC must be ensured.
- 48. All activities / mitigative measures proposed by PP in Environmental Management Plan and approved by SEAC must be ensured.
- 49. All parameters listed in Environmental Monitoring Plan approved by SEAC must be monitored at approved locations and frequencies.
- 50. Project Proponent has to strictly follow the direction/guidelines issued by MoEF, CPCB and other Govt. agencies from time to time.
- 51. The funds earmarked for environmental protection measures shall be kept in separate account and shall not be diverted for other purpose. Year wise expenditure shall be reported to the MoEF, GoI, and its Regional Office located at Bhopal.
- 52. The Ministry or any other competent authority may alter/modify the conditions or stipulate any further condition in the interest of environment protection.

The same of the sa

- 53. The Environmental Clearance shall be valid for a period of seven years from the date of issue of this letter.
- 54. The Project Proponent has to upload soft copy of half yearly compliance report of the stipulated prior environmental clearance terms and conditions on 1st June and 1st December of each calendar year on MoEF & CC web portal http://www.environmentclearance.nic.in/ or http://www.efclearance.nic.in/ and submit hard copy of compliance report of the stipulated prior environmental clearance terms and conditions to the Regulatory Authority also.
- 55. The Regional Office, MoEF, Gol, Bhopal and MPPCB shall monitor compliance of the stipulated conditions. A complete set of documents including Environment Impact Assessment Report. Environmental Management Plan and other documents information should be given to Regional Office of the MoEF, Gol at Bhopal and MPPCB.
- 56. The Project Proponent shall inform to the Regional Office, MoEF, Gol, Bhopal and MP PCB regarding date of financial closures and final approval of the project by the concerned authorities and the date of start of land development work.
- 57. The SEIAA of M.P. reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the environment clearance under the provisions of the Environmental (Protection) Act, 1986, to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.
- 58. All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Fire Department, Civil Aviation Department, Forest Conservation Act, 1980 and Wildlife (Protection) Act, 1972 etc. shall be obtained (as and when applicable), by the project proponent from the respective competent authorities.
- 59. These stipulations would be enforced among others under the provisions of Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and control of Pollution) act 1981, the Environment (Protection) Act, 1986, the Public Liability (Insurance) Act, 1991 and EIA Notification, 2006.
- 60. The proponent shall upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCB. The criteria pollutant levels namely; SPM, RSPM, SO2, NOx (ambient levels as well as stack emissions) or critical sectoral parameters, indicated for the project shall be monitored and displayed at a convenient location near the main gate of the company and in the public domain.
- 61. The environmental statement for each financial year ending 31st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of EC conditions and shall also be sent to the Regional Office of MoEF.

Sy?

Case No. 5804/2018

Issued vide letter no. dated

- 62. Concealing factual data or submission of false/fabricated data and failure to comply with any of the conditions mentioned above may result in withdrawal of this clearance and attract action under the provisions of Environment (Protection) Act, 1986.
- 63. A copy of the environmental clearance shall be submitted by the Project Proponent to the Heads of the Local Bodies, Panchayat and municipal bodies as applicable in addition to the relevant officers of the Government who in turn has to display the same for 30 days from the date of receipt.
- 64. The Project Proponent shall advertise at least in two local newspapers widely circulated, one of which shall be in the vernacular language of the locality concerned, within 7 days of the issue of the clearance letter informing that the project has been accorded environmental clearance and a copy of the clearance letter is available with the State Pollution Control Board and also at website of the State Level Environment Impact Assessment Authority (SEIAA) at www.mpseiaa.nic.in and a copy of the same shall be forwarded to the Regional Office, MoEF, Gol, Bhopal.
- 65. Any appeal against this prior environmental clearance shall lie with the Green Tribunal, if necessary, within a period of 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010.

2126

Endt No. Copy to:- / SEIAA/ 2019

Dated 1.2.19

(Jitendra Singh Raje) Member Secretary

 Principal Secretary, Urban Development & Environment Deptt. 3rd Floor, Mantralaya Vallabh Bhawan, Bhopal.

- 2. Secretary, SEAC, Research and Development Wing Madhya Pradesh Pollution Control Board, Paryavaran Parisar, E-5, Arera Colony Bhopal-462016.
- Member Secretary, Madhya Pradesh Pollution Control Board, Paryavaran Parisar, E-5, Arera Colony, Bhopal-462016.
- 4. The Collector, Distt-Indore -M.P.
- 5. The Commissioner, Municipal Corporation, Indore, MP
- 6. The Jt. Director, Town & Country Planning, Housing Board Complex, A.B. Road, Indore (M.P.)
- Director, I.A. Division, Monitoring Cell, MoEF, Gol, Ministry of Environment & Forest Indira Paryavaran Bhawan, Jor Bagh Road, New Delhi – 110 003
- 8. Director (S), Regional office of the MOEF, (Western Region), Kendriya Paryavaran Bhawan, Link Road No. 3, Ravi Shankar Nagar, Bhopal-462016.

9. Guard file.

(Dr. Sanjeev Sachdev) Officer-in-Charge

Case No. 5804/2018

Issued vide letter no. dated