

State Environment Impact Assessment Authority, M.P. (Government of India, Ministry of Environment & Forests)

Environmental Planning & Coordination Organization

Paryavaran Parisar, E-5. Arera Colony Bhopal-4620 16 visit us http://www.mpseiaa.nic.in Tel:0755-2466970, 2466859 Fax: 0755-2462136

No: 1532 /SEIAA/18 Date: 12.10.18

To,

M/S. D.P. Rai, "Nanhaka", 10, East High Court Road, Ramdeshpeth, Nagpur (M.S)

Sub: Case No.5168/2016 -Prior Environmental Clearance for Manganese Ore mine (Open cast & Underground other than fully mechanized method) in an area of 4.232 Ha. for expansion in production from 2,000 to 3,600 TPA at Khasra no. 1 P, 2P, 4P, 9P,10P & 11P at Village Pandharwani, Tehsil Khairlanji, District Balaghat (MP) by M/S. D.P. Rai, "Nanhaka ", 10, East High Court Road, Ramdeshpeth, Nagpur (M.S)

- I. This has reference to your letter received in SEIAA office on 28.04.2016 and subsequent letters seeking Prior Environmental Clearance for the above project under the EIA Notification, 2006. The proposal has been appraised as per prescribed procedure in the light of provisions under the EIA Notification, 2006 on the basis of the mandatory documents enclosed with the application viz., the Form I, Pre-Feasibility Report, ToR and subsequently submission of EIA, Public Hearing and the additional clarifications furnished in response to the observations of the State Expert Appraisal Committee (SEAC) and State Environment Impact Assessment Authority (SEIAA) constituted by the competent Authority.
- II. It has been noted that the proposal is for Manganese Ore mine in an area of 4.232 ha. The mining lease area is located at khasra no 1 P, 2P, 4P, 9P,10P & 11P at Village-Pandharwani, Tehsil Khairlanji, District Balaghat. The nearest village Jaitpur Khapa is located at the distance of 0.25 km & the nearest village pond is located at the distance 0.40 km. There is no National Park/Sanctuary within 10 Km radius. There is no forest boundary within 250m from mining site.

The proposed project is for expansion in production from 2,000 to 3,600 TPA. The mining will be carried out by Open cast & Underground other than fully mechanized method. The water requirement is 75 KLD. The water met from mine sump, settling tank & well will be used for domestic purpose, dust suppression and green belt development. An area of 3.9887 ha area shall be covered under plantation and 8000 sapling shall be planted. The public hearing was conducted at village Pandharwani on 18.03.2017 at Mine Parisar.

- III. The project has been considered in accordance with the provisions of the EIA notification issued by the Ministry of Environment & Forests vide S.O. 1533 (E), dated 14th September 2006.
- IV. Based on the information submitted, as at Para (II) above and others the State Level Environment Impact Assessment Authority (SEIAA) considered the case in its 503rd meeting dtd. 18.09.2018 and decided to accept the recommendations of 326th SEAC meeting dtd.21.08.2018.

32

Hence, Prior Environmental Clearance is granted for Manganese Ore mine (Open cast & Underground other than fully mechanized method) in an area of 4.232 Ha. for expansion in production from 2,000 to 3,600 TPA at Khasra no. 1 P, 2P, 4P, 9P,10P & 11P at Village Pandharwani, Tehsil Khairlanji, District Balaghat (MP) for the lease period to M/S. D.P. Rai, "Nanhaka", 10, East High Court Road, Ramdeshpeth, Nagpur (M.S), subject to the following specific conditions as recommended by SEIAA & SEAC and subsequent Standard Conditions.

A. SPECIFIC CONDITIONS

- Before commencing any mining activity fencing shall be carried out all around the lease area. Proper watch and ward arrangements should be made with installation of signage at 4 corners of lease area to avoid any untoward incident involving public and animals by the PP.
- Plantation programme as mentioned in EIA/EMP and presented during presentation in SEIAA & SEAC shall be followed in content and spirit.
- PP shall demarcate a barrier zone of 7.5 m as no mining zone in the periphery of mining lease area and develop a green belt. Three row plantation shall be carried out in the greenbelt area in current year with proper watering arrangement.
- 4. The mining operation shall be restricted to above ground water table and in no case it should intersect the ground water table. In case of working below the ground water table approval of the Central Ground Water Board shall be obtained.
- PP will plant 3 years old 1000 trees samplings of suitable indigenous fast grow tree species (neem, amla, ashok, drumstick etc.) towards the habitation site and in barrier zone/no mining zone during first year.
- Emissions from the plant operations including crusher, screens, conveyor transfer points and storage facilities have to be checked through installation of wet dust suppression systems.
- Controlled blasting techniques with sequential drilling shall be adopted as per the guideline of Explosive Deptt.
- PP shall ensure to construct and maintained approach road from the mine site.
 Plantation will be carried out on both side of the approach road. PP shall also ensure
 maintenance of existing pakka road in consultation with competent authority.
- The over burden and waste will be stacked for five years and then simultaneously backfilled in the mined out area where plantation will be raised on it.
- 10. No overburden will be dumped outside the mine lease area.
- 11. Regular air & water quality monitoring shall be carried out by PP before discharging it into the nearby agriculture fields from authorized laboratory in consultation with Regional Officer, MPPCB.
- 12. PP shall ensure generation of employment opportunities nearby Village on priority bases.
- 13. Payments of wages to the workers shall be done in consonance with the provisions in the labour laws.
- 14. Proper infrastructure with shelter, drinking water, toilet and first-aid facilities shall be provided for the laborers. A provision should be made to construct a pakka rest shelter along with toilet and drinking water facility.
- 15. PP should also carry out regular sprinkling in the mining lease area to arrest dust emission from mining activities affecting the nearby agriculture fields

Page 2 of 1

- 16. Mining shall be limited to the area as shown in surface plan and as per the approved mining scheme.
- 17. PP shall ensure the proper water supply arrangements for plantation especially in summer season.
- 18. PP shall ensure proper implementation of plantation, dust suppression, construction of approach road and maintenance of existing pakka road as part of Environmental Management Plan. Additional budget provision shall be made as part of EMP.
- 19. PP must ensure implementation of the following activities with separate budget provision should be kept under CSR.
 - a) PP shall provide separate two toilet facility for man & two toilet facility for women with proper arrangement of water (i.e, Water tanks) & at its maintainance at nearby villagers Pandarwani Tola ,Pandarwani & Miragpur
 - b) Providing financial support to the village school, Computer & Computer Room at village Pandarwani & Miragpur.
 - c) Medical Health check up facility, first aid & other welfare activities for nearby villagers Jaitpur Khapa, Pandarwani Tola ,Pandarwani & Miragpur.

All the modification to the above activities can be made with the permission of the district administration and need based activity for the development of nearby villages shall be implemented by PP in consultation with the District Collector and Grampanchayat.

20. PP should ensure to submit half yearly compliance report and CSR activity report with photographs of plantation in MP-SEIAA.

B. PRE-MINING PHASE

- 21. The lease boundary should be clearly demarcated at site with the given co-ordinates by pillars.
- 22. PP shall demarcate a barrier zone of 7.5 m as no mining zone in the periphery of mining lease area and develop a green belt excluding of the barrier zone of 14.90 ha which has been amalgamated with the subject proposal.
- 23. Necessary consents for proposed activity shall be obtained from MPPCB and the air / water pollution control measures have to be installed as per the recommendation of MPPCB.
- 24. Authorization (if required) under Hazardous and Other Wastes (Management and Transboundary Movement) Rules, 2016 should be obtained by the PP if required.
- 25. PP will also carry out common fencing all around the lease area of 14.90 ha and 4.232 ha.
- 26. If any tree uprooting is proposed necessary permission from the competent authority should be obtained for the same.
- 27. For dust suppression, regular sprinkling of water shall be undertaken.
- 28. Tar/WBM road of 350 mts for carrying out the transportation shall be constructed prior to operation of mine.
- 29. PP will obtain other necessary clearances/NOC from respective authorities.

Sy .

C. MINING OPERATIONAL PHASE

- 30. The distance between underground working and float ore working shall be maintained at 60 mtrs as per statutory provision.
- 31. PP should Construct garland drain all along the lease area and OB dumps with total 08 number of settling pits with in drain and proposed to connect drains to large settling tanks through these pits to avoid silt discharge from open ended drains. PP should ensure zero discharge from the mined area. Apart from existing garland drain, following drain shall be constructed as proposed:1000x 0.25 x 0.50, 500.0 X 0.25X 0.50, 275.0 X 0.25X 0.50
- 32. Following setting tanks shall be constructed apart from the existing tanks for better management of water environment, 10.0L x 5.0W x 5.0m D, 10.0L x 5.0W x 5.0m D, 1.0ha x 5.0m D
- 33. PP shall ensure to conduct a regular monitoring of ground water level with in 2 km radius of mining lease area.
- 34. PP shall carry out subsidence study once in year and report shall be submitted MPSEIAA/ SEAC
- 35. Tar/WBM road of 350 mts for carrying out the transportation shall be constructed prior to operation of mine.
- 36. Provision of solar pumps shall be made for various purposes during mining operation.
- 37. Curtaining of site shall be done through thick plantation all around the boundaries of all part of lease. The proposed plantation scheme should be carried out along with the mining and PP would maintain the plants for five years including casualty replacement. Initially, dense plantation shall be developed along the site boundary (in three rows) to provide additional protection in one year only.
- 38. Plantation on 3.9887 ha areas with 8000 numbers of tree and additional plantation of -280 should be done on both side of the transport road shall be carried out to lessen the air pollution and enhance aesthetic beauty of the area plantation Program as mentioned in EIA/EMP and presented during presentation in SEIAA & SEAC shall be followed in content and sprit.
- 39. Transportation of material shall be done in covered vehicles.
- 40. Transportation of minerals shall not be carried out through forest area.
- 41. PP should follow all safely measures mentioned in DGMS norms.
- 42. Vibration study of the area shall be carried out in consultation with the stakeholders through any authorized technical institution to mitigate the concern raised.
- 43. The ventilation surveys will be conducted in each quarter.
- 44. Periodic maintenance of haulage and village road will be carried out.
- 45. Proper care and safety precaution through intermittent studied shall be undertaken to avoid any land subsidence and void created after exploration of ore will be filled properly by mine waste/sand/fly ash/slag/tailing waste etc as per approved mine plan.
- 46. During the proposal period, exiting dump will be rehandled and same will be used for backfilling in the adjacent/contiguous mine of the same lessee
- 47. Water sprinkling through tankers should be provided on 500 meter long and 06 meter wide haul road. However, regular water spraying should also be practiced on 70 meters long and width 06 meters wide transport road for dust suppression.

afe

- 48. All garland drains shall be connected to settling tanks through settling pits and settled water shall be used for dust suppression, green belt development and beneficiation plant. Regular de-silting of drains and pits should be carried out.
- 49. The existing and proposed land use plan of the mine is as follows:

Items	Existing	Conceptual Period
Total lease area	4.232 ha	
Area under dumps	0.20 ha	Nil
Area under sub grade dump	Nil	Nil
Area under pits	1.1109ha	3.0831 ha
Infrastructure & Road	0.20 ha	Nil
Mineral storage	Nil	0.14ha
Plantation	Nil	1.00 ha
Un-worked area	2.7211ha	0.0089ha
Total	4.232ha	4.232ha
Water body	0.50ha	0.0944ha
Area to be reclaimed	Nil	2.9887ha
Plantation	Nil	3.9887ha (8000No.)
Un worked area	Nil ·	1.00ha (2000 No.)
Backfilled area	Nil	2.9887ha (6000 no.)

Any change in conceptual land use shall be intimated to SEIAA.

- 50. Appropriate and submitted activities shall be taken up for social up-liftment of the Region. Funds reserved towards the same shall be utilized through Gram Panchayat. Further any need base and appropriate activity may be taken up in coordination with local panchayat.
- 51. PP will take adequate precautions so as not to cause any damage to the flora and fauna during mining operations.
- 52. The commitments made in the public hearing are to be fulfilled by the PP.
- 53. Fund should be exclusively earmarked for the implementation of EMP through a separate bank account.
- 54. PPE's such as helmet, ear muffs etc should be provide to the workers during mining operations.
- 55. For underground operations, natural ventilation should be provided (Veq at the rate of 0.85 to 0.95) in all working shifts through vertical shaft and main incline and ventilation survey should be conducted on each quarter and flow of air (intake and return) should be monitored on daily basis as per DGMS norms.
- 56. For mining operations following standard illumination should be provided as per DGMS norms.

	For surface Lighting	
For underground Lighting		
SI.No.	Location	Illumination in Lux
	Incline main travelling road way	0.5 lux
2	Incline pit bottom	1.5 lux
3	Vertical shaft bottom	1.5 lux

hy

- 57. For roof support system, as proposal steel roads should be at least 1.50 meter long with minimum 20 mm diameter and the diameter of holes should be less than 32mm.the load bearing capacity of each bolt shall be at least 02 tones of load in one hour, 04 tones of load in 04 hours and 06 tones of load in 08 hours.
- 58. The back of excavated area shall be supported by fully grouted cable bolts of 12 mm at an interval of 2.0 m X 2.0m in a grid pattern with one additional 2.0 m long fully grouted rock bolt in the center of the grid. Diameter of each cable bolt shall be at least 16 mm and cables bolts shall be installed in the back of the stope in such manner that its length in the back at no time shall be less than 4.0 m (for 8.0 m wide stops) and 6.0 m (for 22.0 m wide stops). Each cable bolt shall be capable of bearing at least 25 tones of load.
- 59. The hanging wall shall be supported by fully rock bolts at least 2.0 m long at maximum interval of 2.0m X 2.0m in grid pattern. The bolts shall be installed perpendicular to the foliation plan of rocks mass with one row of chocks shall be provided at an interval of 3.0 meter all along the hang wall side in the stope as and when required. Similarly, additional rack bolts shall be provided as and when required.
- 60. The freshly exposed footwall area shall be supported with cable bolts of suitable length and the distance between the cable bolt and footwall shall in no case be more than 2.0 m if required, inclined cable bolts shall also be provided to ensure the same. if clay bands/geological disturbances exposed in footwall, the side shall be immediately supported by 2.0 m long fully grouted steel bolts in a grid pattern of 2.0 m X 2.0 m. The bolts shall be installed perpendicular to foliation of the rock mass.
- 61. Wet drilling system and controlled NONAL blasting with low charge (if requited) as prescribed by DGMS should be practiced.
- 62. As proposed by PP, safety distance of 100 m between u/g and o/c operation shall be maintained to prevent entering of water in u/g operation. In this regard all the norms stipulated by DGMS should be complied.
- 63. Sand stowing shall be carried out as per the plan submitted in EIA using sand and fly ash. Any other material such as tailing waste or slag should be used with sand for stowing only after confirming its suitability by lechate study.
- 64. Blast vibration study should be carried out once in a year and their record shall be maintained.
- 65. PP should carryout load testing after one hour of bolting.

D. ENTIRE LIFE OF THE PROJECT

- 66. Proper infrastructure with shelter, Drinking water, Toilet and first-aid facilities shall be provided for the laboures. A provision should be made to construct a pucca rest shelter of 8m x 6m along with toilets and drinking water facility
- 67. Condition of existing settling pits should be improved and stone pitching should be carrying out for their stability.
- 68. Separate cell be constructed for environment management, complaints and grievances nd compliance of conditions
- 69. The proposed EMP cost is Rs. 26.20 lacks and Rs. 14.87 lacks /year are proposed as recurring expenses out of which Rs11.20 lacks is proposed for green belt development expenses for plantation in the proposed EMP of this project.

Page 6 of 11

- 70. Under CSR activity, Rs. 2.50 lacks and Rs. 7 lacks /year are proposed as recurring expenses in different activities and should be implemented through respective committees.
- 71. The adequate budget shall be provided for the PH issue i.e. construction of road , provision of hand pump , (16.50 Lacs) and protection measures like construction of retaining wall etc .
- 72. The environment policy of the company should be framed as per MoEF&CC guidelines and same should be implemented through monitoring cell. In case the allocated EMP budget for mitigative measures to control the pollution is not utilized fully, the reason of under utilization of budgetary provisions for EMP should be addressed in annual return.
- 73. A separate bank account should be maintained for all the expenses made in the EMP activities by PP for financial accountability and these details should be provided in Annual Environmental Statement.
- 74. PP shall be responsible for discrepancy (if any) in the submissions made by the PP to SEAC & SEIAA.
- 75. PP will comply with all the commitments made vide letter dated 21.08.2018.
- 76. The validity of the EC shall be as per the provisions of EIA Notification subject to the following: Expansion or modernization in the project, entailing capacity/ built-up area/ project area, addition with change in process and or technology and any change in product mix in proposed mining unit shall require a fresh Environment Clearance.

E. STANDARD CONDITIONS

- All activities / mitigative measures proposed by PP in Environmental Impact Assessment and approved by SEAC must be ensured.
- All activities / mitigative measures proposed by PP in Environmental Management Plan and approved by SEAC must be ensured.
- 3. All parameters listed in Environmental Monitoring Plan approved by SEAC must be monitored at approved locations and frequencies.
- 4. Blast vibrations study shall be conducted and submitted to the Regional Office, MoEF, Gol, Bhopal and MP PCB within six months. The study shall also provide measures for prevention of blasting associated impact on nearby houses and agricultural fields.
- Controlled blasting techniques with sequential drilling shall be adopted. The blasting shall be carried out in the day time only.
- 6. Slope of the mining bench and ultimate pit limit shall be as per the mining scheme approved by Indian Bureau of Mines.
- A final mine closure plan, along with details of Corpus Fund, shall be submitted to the Regional Office, MoEF, Gol, Bhopal and MP PCB within 5 years in advance of final mine closure for approval.
- 8. No change in the calendar plan including excavation, quantum of mineral and waste shall be made.
- Mining will be carried out as per the approved mining plan. In case of any violation of mining plan, the Environmental Clearance given by SEIAA will stand cancelled.
- Adequate buffer zone shall be maintained between two consecutive mineral bearing deposits.

of a

- 11. The transportation of the minerals extracted from the mining area shall be limited to day hours time only.
- Maintenance of near by local roads through which transportation of minerals are undertaken shall be carried out by the company regularly at its own expenses. The roads shall be black topped.
- 13. Measures for prevention and control of soil erosion and management of silt shall be undertaken. Protection of dumps against erosion shall be carried out with geo textile matting or other suitable material, and thick plantations of native trees and shrubs shall be carried out at the dump slopes. Dumps shall be protected by retaining walls.
- 14. Trenches / garland drains shall be constructed at foot of dumps and coco filters installed at regular intervals to arrest silt from being carried to water bodies. Adequate number of check dams and gully plugs shall be constructed across seasonal/ perennial Nallahs, if any, flowing through the ML area and silts arrested. De- silting at regular intervals shall be carried out.
- 15. The project proponent will ensure necessary protection measures around the mine pit, waste dumps and garland drain.
- 16. Top soil / solid waste shall be stacked properly with proper slope and adequate safeguards and shall be utilized for backfilling (wherever applicable) for reclamation and rehabilitation of mined out area. Top soil shall be separately stacked for utilization later for reclamation and shall not be stacked along with over burden.
- 17. Over burden (OB) shall be stacked at earmarked dump site(s) only and shall not be kept active for long period. The maximum height of the dump shall not exceed 20 m, each stage shall preferably be of maximum 10 m and overall slope of the dump shall not exceed 35o. The OB dump shall be backfilled and shall be scientifically vegetated with suitable native species to prevent erosion & surface run off.
- 18. Monitoring and management of rehabilitated areas shall continue until the vegetation becomes self-sustaining. Compliance status shall be submitted to the Regional Office, MoEF, Gol, Bhopal and MP PCB on six monthly basis.
- 19. Green belt development shall be carried out considering CPCB guidelines including selection of plant species and in consultation with the local DFO / Agriculture Deptt. Herbs & shrubs shall also form a part of afforestation programme besides tree plantation. The company shall involve local people for plantation programme. Details of year wise afforestation programme including rehabilitation of mined out area shall be submitted to the Regional Office, MoEF, Gol, Bhopal and MP PCB every year.
- 20. Vehicular emissions shall be kept under control and regularly monitored. Vehicles used for transportation of minerals and others shall have valid permissions as prescribed under Central Motor Vehicle Rules, 1989 and its amendments. The vehicles transporting minerals shall be covered with a tarpaulin or other suitable enclosures so that no dust particles / fine matters escape during the course of transportation. No overloading of minerals for transportation shall be committed. The trucks transporting minerals shall not pass through wild life sanctuary, if any in the study area.
- 21. Four ambient air quality-monitoring stations shall be established in the core zone as well as in the buffer zone for RSPM, SPM, SO2, NOx monitoring. Location of the stations should be decided based on the meteorological data, topographical features and environmentally and ecologically sensitive targets and frequency of monitoring should be undertaken in consultation with the State Pollution Control Board. The monitored data for criteria pollutants shall be regularly up-loaded and displayed on the company's website.
- 22. Data on ambient air quality (RPM, SPM, S02, NOx) should be regularly submitted to the Regional office, MoEF, Gol, Bhopal and the State Pollution Control Board / Central Pollution Control Board once in six months.



- 23. Ambient air quality at the boundary of the mine premises shall confirm to the norms prescribed in MoEF notification no. GSR/826(E) dtd. 16.11.09.
- 24. Fugitive dust emissions from all the sources shall be controlled. Water spraying arrangement on haul roads, loading and unloading and at transfer points shall be provided and properly maintained. The dust emission shall be monitored regularly as per norms and records to be submitted to the Regional Office, MoEF, Gol, Bhopal and MP PCB regularly.
- 25. Measures shall be taken for control of noise levels below 75 dBA in the work environment. Workers engaged in operations of HEMM, etc., shall be provided with ear plugs / muffs and health records of the workers shall be maintained.
- 26. Rain water harvesting shall be undertaken to recharge the ground water source. Status of implementation shall be submitted to the Regional Office, MoEF, Gol, Bhopal and MP PCB within six months and thereafter every year from the next consequent year.
- 27. Regular monitoring of ground and surface water sources for level and quality shall be carried out by establishing a network of existing wells and constructing new piezometers during the mining operation. The monitoring shall be carried out four times in a year i.e. pre-monsoon (April-May), monsoon (August), post-monsoon (November) and winter (January) and the data thus collected shall be regularly sent to Regional Office, MoEF, Gol, Bhopal, MP PCB, Central Ground Water Authority and Regional Director, Central Ground Water Board.
- 28. The waste water from the mine if any, shall be treated to conform to the standards prescribed under GSR 422 (E) dated 19th May, 1993 and 31st December, 1993 or as amended from time to time. The oil and grease trap shall be installed for the effluents generated from the workshop, if any, before discharging into the natural stream. The discharged water from the tailing dam, if any shall be regularly monitored and report submitted to the Regional Office, Ministry of Environment & Forests, Gol, Bhopal, Central Pollution Control Board, and the State Pollution Control Board.
- 29. Hydro-geological study of the area shall be reviewed by the project proponent annually. In case adverse effect on ground water quality and quantity is observed mining shall be stopped and resumed only after mitigating steps to contain any adverse impact on ground water is implemented.
- 30. Occupational health check up for the workers including identification of work related health hazards, training on malaria eradication, HIV, and health effects on exposure to mineral dust etc. shall be carried out. Periodic monitoring for exposure to respirable mineral dust on the workers shall be conducted and records maintained including health records of the workers. Awareness programme for workers on impact of mining on their health and precautionary measures like use of personal equipments etc. shall be carried out periodically. Review of impact of various health measures shall be conducted followed by follow up action wherever required. It should be made available for inspection whenever asked. Necessary funds for this also should be earmarked.
- 31. Project Proponent shall ensure appropriate arrangement for shelter and drinking water for the mine workers.
- 32. Persons working in dusty areas shall be provided with protective respiratory devices and they shall also be imparted adequate training and information on safety and health aspects.
- 33. Commitment towards CSR have to be followed strictly.
- Special measures shall be adopted to prevent the nearby settlements from the impacts of mining activities.

de

- 35. The Project Proponent shall inform to the Regional Office, MoEF, Gol, Bhopal and MP PCB regarding date of financial closures and final approval of the project by the concerned authorities and the date of start of land development work.
- 36. The necessary funds as per mandate shall kept for environmental protective measures which should be kept in separate account and shall not be diverted for other purpose. Year wise expenditure shall be reported to the Regional Office, MoEF, Gol, Bhopal and MP PCB.
- 37. The Regional Office, MoEF, Gol, Bhopal and MP PCB shall monitor compliance of the stipulated conditions. A complete set of documents including Environment Impact Assessment Report, Environmental Management Plan, Public hearing and other relevant documents should be given to Regional Office, MoEF, Gol, Bhopal and MP PCB.
- 38. A copy of the environmental clearance shall be submitted by the Project Proponent to the Heads of the Local Bodies, Panchayat and Municipal Bodies, as applicable, in addition to the relevant officers of the Government who in turn has to display the same for 30 days from the date of receipt.
- 39. The Project Proponent shall advertise at least in two local newspapers widely circulated, one of which shall be in the vernacular language of the locality concerned, within 7 days of the issue of the clearance letter informing that the project has been accorded environmental clearance and a copy of the clearance letter is available with the State Pollution Control Board and also at web site of the State Level Environment Impact Assessment Authority (SEIAA) website at www.mpseiaa.nic.in and a copy of the same shall be forwarded to the Regional Office, MoEF, Gol, Bhopal.
- 40. The project proponent has to strictly follow directions/guideline issued by the MoEF, Gol, CPCB and other Govt. agencies from time to time.
- 41. Action plan with respect to suggestion/improvement and recommendations made and agreed during public hearing consultation shall be submitted to the Regional Office, MoEF, Gol, Bhopal, MP PCB and to the competent authority of the State Govt. within six months.
- 42. The Project Proponent has to submit half yearly compliance report of the stipulated prior environmental clearance terms and conditions in hard and soft copy to the Regulatory Authority on 1st June and 1st December of each calendar year.
- 43. The SEIAA of M.P. reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the environment clearance under the provisions of the Environmental (Protection) Act, 1986, to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.
- 44. These stipulations would be enforced among others under the provisions of Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and control of Pollution) Act 1981, the Environment (Protection) Act, 1986, the Public Liability (Insurance) Act, 1991 and EIA Notification, 2006.
- 45. The Ministry or any other competent authority may alter/modify the conditions or stipulate any further condition in the interest of environment protection.
- 46. Concealing factual data or submission of false/fabricated data and failure to comply with any of the conditions mentioned above may result in withdrawal of this clearance and attract action under the provisions of Environment (Protection) Act, 1986.
- 47. Any appeal against this prior environmental clearance shall lie with the Green Tribunal, if necessary, within a period of 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010.

off

- 48. All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Fire Department, Civil Aviation Department, Forest Conservation Act, 1980 and Wildlife (Protection) Act, 1972 etc. shall be obtained, as applicable by project proponents from the respective competent authorities.
- 49. The proponent shall upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCB. The criteria pollutant levels namely; SPM, RSPM, SO2, NOx (ambient levels as well as stack emissions) or critical sectoral parameters, indicated for the project shall be monitored and displayed at a convenient location near the main gate of the company in the public domain.
- 50. The environmental statement for each financial year ending 31st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of EC conditions and shall also be sent to the Regional Office of MoEF.

/SEIAA/18 Dated: 12.10.18 Copy to:-

(Jitendra Singh Raje)

- 1. Principal Secretary, Department of Environment, Government of Madhya Pradesh,
- 2. Secretary, SEAC, Research and Development Wing Madhya Pradesh Pollution Control Board, Paryavaran Parisar, E-5. Arera Colony Bhopal-4620 16
- 3. Member Secretary, Madhya Pradesh Pollution Control Board, Paryavaran Parisar, E-5,
- 4. Collector, District Balaghat, M. P.
- 5. Divisional Forest Officer, District Balaghat, M. P.
- 6. I.A. Division, Monitoring Cell, MoEF& CC, Gol, Indira Paryavaran Bhawan, Jor Bagh
- 7. Director (S), Regional office of the MoEF, Western Region, Kendriya Paryavaran Bhawan, Link Road No. 3 Ravi Shankar Nagar, Bhopal-462016.
- 8. Director, Geology & Mining, Madhya Pradesh, 29-A, Khanij Bhawan, Arera Hills, Bhopal
- 9. District Mining Officer, District Balaghat, M. P.
- 10. DEO, SEIAA for upload on website. 11. Guard file

(Dr Sanjeev Sachdev) Officer-in-Charge